

Multi Light Colour Viewing Booth

(標準光源)



Production and Lab (Width : 100cm)

섬유,플라스틱,페인트,잉크등 칼라관련 산업에서 표준광원을 이용한 색상확인 및 교정은 그 중요성과 필요성이 날로 증가하고 있으며, 바이어들의 색상확인도 점차 까다로워지고 있다.

또한 기업은 글로벌체제하에서, 각종 하청 및 부품의 조달을 전세계로 확대되고 있으며, 각각의 하청 및 부품업체는 발주업체가 요구하는 색상을 충족시키기 위해 표준광원하에서 색상확인을 하여야 함은 극히 당연한 일로 받아들여지고 있다.

모델 **LUX** 는 큰사이즈 샘플의 색상확인이 용이하도록 제작되었다.

Checking colors under the standard illuminants is the most important thing in a Plastic or Textile Industries. Buyers are more critical and selective on color verification. Subcontracting factories for the components are spreading all over the world.

Therefore, subcontractors view color confirmation as a matter of fact.

The model **LUX** is designed to check color suitable for the large size samples.

Standard(6 kinds of illuminants) D65, CWF, A, TL84, U30, UV

MULTI LIGHT COLOUR VIEWING BOOTH

Multi Light Colour Viewing Booth



光源 (Light Source)

STANDARD(6 Lamps)

- DayLight (CIE D65)
Average North Sky Daylight at 6500 °K
- Cool White (CWF, CIE F2)
Commonly used in office and store at 4150 °K
- Incandescent A
Typical home lighting at 2856 °K
- Tri-phosphor (TL84, CIE F11)
Commonly used in Europe at 4100 °K
- Ultralume 3000 (U30, CIE F12)
Commonly used in America at 3000 °K
- Ultra Violet (BLB)
Check optical brighteners, whitening agents
fluorescent pigments & dyes.
Use together with other lamps

OPTIONAL

- DayLight (D75)
North sky Daylight at 7500 °K
- DayLight (D55)
Noon sky Daylight at 5500 °K
Commonly used for artificial daylight
- DayLight (D50)
Noon sky Daylight at 5000 °K
Commonly used in graphic arts
- TL83, TL85
Tri-phosphor fluorescent at 3000 °K
Tri-phosphor fluorescent at 5000 °K

應用分野 (Application)

섬유,잉크,페인트,플라스틱,가구,종이,화장품,목재,유리,세라믹,코팅,포장,식품,관능검사,인쇄,패션등
Textile, Inks, Paints, Plastic, Paper, Furniture, Colorants, Pigments, Wood, Glass, Ceramics,
Cosmetics, Coatings, Printing, Packaging, Advertising, Graphic Design, Interior Fashion Design

製品辭讓 (Specifications)

액정 표시장치 : 광원명, 색온도, 광원별 사용시간 등을 실시간으로 Display
Display (LCD) : Display name of illuminants, Color Temperature, used time of each illuminants
Colour : Internal & External - Munsel N7 Natural Grey (Lusterless, 無光澤)
Select Switch : Membrane Switch
Viewing Table : 45°, 600×320×230mm(W×D×H)
External Area : 1000×680×800mm(W×D×H)
39.3" × 26.7" × 31.5"
Viewing Area : 960×660×560mm(W×D×H)
38.2" × 25.9" × 22.0"
Weight : 70Kg
Total Shipping Weight : 90Kg
Voltage : 100~120, 220~240VAC. 50/60Hz



Agent

Manufacturer

BOWOO ENG CO., LTD

ADDR: 719-3, GUMJUNG, GUNPO, GYUNGKI, KOREA

TEL : (031)455-0291 FAX : (031)459-2301

E-mail : bowooeng@boteck.com

http : //www.boteck.com